

elipson® | A680

6 CHANNEL - POWER AMPLIFIER

High Audio performances
with large power,
elegant and perfect
versatility

- 6 channel – 3 in stereo
- (Total power of 480 W @ 4 Ohms)
- 3 Zones
- 2 Bus inputs
- 2 Bus outputs to connect more A680 multi-channel amplifiers
- Perfect flexibility for audio signal input :
Switch for common audio signal (Bus) or individual stereo channel (line) for each zone
- 6 Individual adjustment for voltage input
- Trigger mode / auto mode / automatic Standby mode
- Stereo / Bridge mode
- (up to 3 x 150 W @ 8 Ohms)



TECHNICAL

Type
Multi-zones power amplifier

Channel
6 channel, 3 zones

Power output
80 watts / canal @ 4 Ohms

Bridged power output
150 watts / canal @ 8 Ohms

Total harmonic distortion
<1% 1 kHz / 80 W / 4 Ohms

Channel separation
> 65 dB / 1 kHz 4 Ohms Zone-Zone

Signal to noise
> 90 dB (A weighted Ref : 19 V)

Frequency range
20 Hz - 20 kHz (+/- 3 dB)

Trigger
12V IN & OUT

Damping Factor
> 55 (1 kHz)

Input impedance
> 20 k Ohms

Voltage input
AC 100 - 120 V 60 Hz / AC 220 - 240 V
50 Hz Auto Switching

Safety
CE, CB, NRT, FCC, CE-EMC, ERP

ACCESSORY



Supplied with mounting
brackets for Audio Video
Racks Thickness: 2U

DIMENSIONS WEIGHT

Dimensions
W x H x D : 430 x 88* x 335 mm

Weight
9,5 kg

*without feet

PACKAGING

Dimensions inner box
W x H x D : 545 x 120 x 418 mm

Gross weight
11,7 kg

Dimensions outer box
W x H x D : 560 x 433 x 210 mm

PRODUCT CODES

SKU
ELIAMP680

EAN
3700795192047