

DMP-A8

[Overview \(/Product/index/model/DMP-A8/target/uXoirEESmeVKKmVViAFMcQ%3D%3D.html\)](/Product/index/model/DMP-A8/target/uXoirEESmeVKKmVViAFMcQ%3D%3D.html)

[Specs \(/Product/spec/model/DMP-A8/target/uXoirEESmeVKKmVViAFMcQ%3D%3D.html\)](/Product/spec/model/DMP-A8/target/uXoirEESmeVKKmVViAFMcQ%3D%3D.html)

[Picture \(/Product/gallery/model/DMP-A8/target/uXoirEESmeVKKmVViAFMcQ%3D%3D.html\)](/Product/gallery/model/DMP-A8/target/uXoirEESmeVKKmVViAFMcQ%3D%3D.html)

[Video \(/Product/video/model/DMP-A8/target/uXoirEESmeVKKmVViAFMcQ%3D%3D.html\)](/Product/video/model/DMP-A8/target/uXoirEESmeVKKmVViAFMcQ%3D%3D.html)

[Reviews \(/Product/reviews/model/DMP-A8/target/uXoirEESmeVKKmVViAFMcQ%3D%3D.html\)](/Product/reviews/model/DMP-A8/target/uXoirEESmeVKKmVViAFMcQ%3D%3D.html)

[Certificate \(/Product/cert/model/DMP-A8/target/uXoirEESmeVKKmVViAFMcQ%3D%3D.html\)](/Product/cert/model/DMP-A8/target/uXoirEESmeVKKmVViAFMcQ%3D%3D.html)

Specs

Model	EVERSOLO DMP-A8
Display	6" LCD touchscreen
Internal Memory	4GDDR4 +64GeMMC
DAC	AK4191EQ+AK4499EX
Audio Processor	XMOS XU316
Op-amp Chip	OPA1612
Power Supply	High-quality, low-noise linear + digital dual power supply
SSD	Support M.2 NVME 3.0 2280 protocol, up to 4TB (SSD isn't included).
USB-A Port	USB3.0*2
Ethernet	RJ-45(10/100/1000Mbps)
WiFi	WiFi 2.4G+5G dual band
Playback and DAC Decoding	Support up to stereo DSD512, PCM 768KHz 32Bit
Music Service	Tidal, Qobuz, Highresaudio, Amazon Music, Deezer, Radio Paradise, WebDAV, UPnP
Streaming	Air Play, DLNA, Tidal Connect etc.
Bluetooth Audio Input	BLuetooth BT5.0, support SBC/AAC/aptX/aptX LL/aptX HD/LDAC
USB-B Audio Input	Supports Windows (10, 11), Android, IOS. Support up to stereo DSD512, PCM 768KHz 32Bit.
Optical/Coaxial Audio Input	Support up to stereo PCM 192KHz 24Bit, Dop64
HDMI ARC	Support up to stereo PCM 192KHz 24Bit
Analog preamp audio input	XLR(Balanced)*1+RCA(Unbalanced), Maximum Gain +10dB
USB Audio Output	Support up to stereo DSD512, PCM 768KHz 32Bit
IIS Output	Support up to stereo DSD512, PCM 768KHz 32Bit
Optical/Coaxial Audio Output	Support up to stereo PCM 192KHz 24Bit, Dop64
Analog Audio Output	Preamp Audio Output:XLR(Balanced)+RCA(UnBalanced)
XLR Output Audio	Output level: 4.2V
Characteristics	Frequency response: 20Hz~20KHz(±0. 25dB) Dynamic range: > 128dB SNR: >128dB THD+N: <0.00009%(-120dB) @No-wt Crosstalk: >-121dB
RCA Output Audio	Output level: 2.1V
Characteristics	Frequency response: 20Hz~20KHz (±0. 25dB) Dynamic range: > 125dB SNR: >125dB THD+N: <0.00010%(-119dB)@A-WT Crosstalk: >-121dB
Control Method	Mobile App, Touch screen control, IR+Bluetooth remote control
PSU	AC 110~240V 50/60Hz
Rated Power	16W
Dimensions	W 388mm*L 248mm* H 90mm
Packing List	Power cable*1, Remote Control*1, Screwdriver*1, user manual*1