

PRODUCT INFORMATION

SV-500MK

Hybrid Integrated Amplifier

The SV-500 MK presents itself in a timeless design and with the typical Vincent sound character. The addition of "MK" in the name makes it clear that there were no fundamental changings made compared to the previous model, true to the motto "Never change a running system!"



However, customer needs require further technical developments. That's why we have revised the connection section of the SV-500 MK. In addition to two analog inputs, an optical and coaxial input, Bluetooth and an HDMI connection (ARC) are now also available.

Two 6N1 tubes and one 12AX7 tube work in the input stage, which process the sound of the music signal. They give the sound the naturalness and warmth that Vincent is used to. The final amplification in the output stage is then made by transistors from Toshiba.





PRODUCT INFORMATION

SV-500MK

Hybrid Integrated Amplifier

A 110 watt toroidal transformer works in the power supply. Capacitors with 20,000 yF are then available for grading the current signal and as a buffer.

Of course, a high-quality aluminum remote control is included in the scope of delivery, which rounds off the elegant appearance.





SV-500MK



Connections

TECHNICAL SPECIFICATIONS

Frequency Response: 20 Hz – 20 kHz ±0.5 dB,

20 Hz - 50 kHz ±2 dB

NOP* RMS/8 Ohm: 2×50 Watt NOP* RMS/4 Ohm 2×80 Watt Input Sensitivity: 420 mV

Total Harmonic Distortion: < 0.1% (1 kHz, 1 Watt)

S/N Ratio: >90dB Input Impedance 47 kOhm

Inputs: 2 x Stereo RCA, 1 x Optical, 1 x Coax,

1 x Bluetooth, 1 x HDMI (ARC)

Outputs: 1 x Stereo RCA Rec Out, 1 x Stereo RCA Pre Out,

2 x Power Control, 2 x 2 Speaker Connectors

Tubes: 1 x 12AX7, 2 x 6N1

Playable Digital Formats: WAV, FLAC, APE, LPCM, MP3, ACC, AC3, WMA

Colour: black / silver
Weight: 10 kg

Dimensions (WxHxD): 430 x 118 x 375 mm

*Nominal Output Power



power**Line**