

SPECIFICATIONS



Stereo Power Amplifier

S-02

SPECIFICATIONS

Spec description

Speaker output	
Rated output power	145W + 145W (8Ω) 290W + 290W (4Ω)
Maximum output power	580W + 580W (2Ω)
Damping factor	1000
Analog audio inputs	
XLR	1 pair
Input impedance	44kΩ
RCA	1 pair
Input impedance	22kΩ
General	
Power supply	
	AC 230V, 50Hz
	AC 120V, 60Hz
	AC 220V, 60Hz
Power consumption	440W (no signal: 160W)
External dimensions (W × H × D)	445 × 221.5 × 489.6mm 17-5/8" × 8-3/4" × 19-3/8" (including protrusions)
Weight	48kg / 105-7/8 lb
Included accessories	Power cord × 1 Power cord support bracket × 1 Power cord support bracket screw × 2



Please choose your language.



International



Audio performance

Frequency response	5Hz to 100kHz (+0dB, -3dB, 8 Ω)
S/N ratio	115dB (IHF-A)
Total harmonic distortion	0.003% (1kHz, 8 Ω , 145W)
Gain	28.5dB

- This product is available in three different power supply variations, as shown in the chart above. Make sure that the voltage shown on the rear panel matches the AC line voltage in your area.
- The shape of the AC inlet and plug of the supplied power cord depends on the voltage rating and destination country.
- Design and specification are subject to change without notice.
- Weight and dimensions are approximate.



Please choose your language.

