

Model	EverSolo DAC-Z6	
Display	3-inch LCD screen	
Screen	Chassis	
Aluminum Alloy		DAC Audio
ES 9068*2		Audio
		Processor
XMOS XU316		OPA Chip
RT 6863*6		Power
		Supply
high quality switching power supply with low noise		Bluetooth
Qualcomm QCC5125 Bluetooth module, BT5.0		Audio Input
Support SBC/AAC/aptX/aptX LL/aptX HD/LDAC		USB-B DAC
Bluetooth protocol		Input
Compatible with Windows (7, 10), Mac, Android		USB-C DAC
and IOS Up to stereo DSD512, PCM 768KHz 32Bit,		Input
MQA		
Compatible with Windows (7, 10), Mac, Android		OPTICAL
and IOS Up to stereo DSD512, PCM 768KHz 32Bit,		Audio Input
MQA		
Up to stereo PCM 192Khz 24Bit, DSD64 Dop,MQA		COAXIAL
		Audio Input
Up to stereo PCM 192Khz 24Bit, DSD64 Dop,MQA		Analog Audio
		Output
Preamp output: XLR(balanced)+RCA		USB Port
Headphone output: 6.3mm single-ended		
USB2.0*1 (only for firmware upgrade)		Control
		Methods

Remote control, Mobile APP control, Knob control

16-300Ω (low gain mode:16-32Ω/high gain mode:32-300Ω)

Output Level(Vrms): 4.1Vrms@0dBFS

THD+N@A-wt: 0.000094%@1kHz
(-120dB@1kHz)

THD+N@No-wt: 0.000117%@1kHz
(-118dB@1kHz)

Noise@No-wt : <3uVrms

SNR@No-wt: 125@1kHz

frequency response: 20Hz-20kHz(±0.15dB)

CROSSTALK: -123dB@1kHz

DNR@No-wt: 125dB@1kHz

Output Level(Vrms): 2.1Vrms@0dBFS

THD+N@A-wt: 0.000116%@1kHz(-118dB@1kHz)

THD+N@No-wt: 0.000138%@1kHz(-117dB@1kHz)

Noise@No-wt : <2.5uVrms

SNR@No-wt: 21dB@1kHz

frequency response: 20Hz-20kHz(±0.15dB)

CROSSTALK: -118dB@1kHz

DNR@No-wt: 121dB@1kHz

Output Level(Vrms): 1.2Vrms@0dBFS

Max Power: : 45 mW@32Ω

THD+N@A-wt: 0.00028%@1kHz(-111dB@1kHz)

THD+N@No-wt: 0.00031%@1kHz(-110dB@1kHz)

Noise@No-wt : <3.5uVrms

SNR@No-wt: 114dB@1kHz

Headphone

Impedance

XLR Audio

Output

RCA Audio

Output

Headphone

(low gain

mode)

Headphone

(high gain

mode)

frequency response: 20Hz-20kHz(±0.15dB)

DNR)@No-wt: 114dB@1kHz

Output Level(Vrms): 2.8Vrms@0dBFS

Power Input

Max Power: 26 mW@300Ω

THD+N@A-wt: 0.00014%@1kHz(-117dB@1kHz)

THD+N@No-wt: 0.00016%@1kHz(-116dB@1kHz)

Noise@No-wt : <3.5uVrms

SNR)@No-wt: 121dB@1kHz

frequency response: 20Hz-20kHz(±0.15dB)

DNR)@No-wt: 121dB@1kHz

AC 110~240V 50/60Hz

Rated power

9W

Product

Dimensions

270mm(W) * 187mm(D)* 50mm(H)

Accessories

Remote control*1, Power cable*1, User manual*1

Exclusive events and announcements.

 (skype:cathy_5787?chat)
Please Enter Your

 (<https://twitter.com/zidoottv>)

Go

 (<https://www.facebook.com/zidoottv>)

