## J L - 1 0 S W

LANDSCAPE SUBWOOFER



#### **SPECIFICATIONS**

FREQUENCY RESPONSE	115Hz-20KHz
DRIVER	10" IMG Dual Voice Coil
SENSITIVITY	90dB (2.83V @ 1m)
IMPEDENCE	70V @ 250W 8 Ohm Stereo 4 Ohm Mono
POWER HANDLING	200W
ENCLOSURE MATERIAL	Canopy: Rustproof, UV Resistant Aluminum Cabinet: Heavy Duty, High Impact Polyethylene
FINISH	Canopy: Metallic Gray Cabinet: Matte Black
DIMENSIONS	555mm H, 409mm W, 409mm D 21.85" H, 16.10" W, 16.10" D
WEIGHT	15.91 kg (35.0 lbs)
ACCESSORIES (SOLD SEPARATELY)	JJB-3 Junction Box (PN: 1063450) JDA-500 DSP Amplifier (120V: 10634321, 230V: 10634322)

# Jamo L A N D S C A P E

#### DESIGN + PERFORMANCE

The half burial design allows for large cabinet volume necessary for low extension and high output, while remaining hidden in its environment. This allows for a superior listening experience while maintaining a high end, modern look in today's finest landscapes and outdoor living spaces.

### HIGH PERFORMANCE

With a long-throw 10" IMG woofer, the JL-10SW landscape subwoofer uses the same high performance acoustic design philosophies of Jamo's legendary indoor products, bringing the world's most natural, powerful, detailed sound to your outdoor living space.

#### 70V COMPATIBLE

For distributed line applications, the JL-10SW uses a transformerless dual voice coil design for 70V operation. Since tranformers severly limit a subwoofer's low frequency capabilities, this unique design is the perfect solution when building a great sounding commerical or large residential system. This design also allows for high performance low impedance operation as well: 8 ohm stereo or 4 ohm mono for the ultimate in system flexibility.

#### ALL WEATHER DURABILITY

A rustproof aluminum top cap and a high impact, polyethylene cabinet provides the utmost in all-weather cabability, while an IP45 rating ensures the JL-10SW is lab tested and certified to offer the best in outdoor audio year in and year out.