

General Specifications

Frequency Response

- 4 Hz – 20 kHz

Audio Dynamic Range

- 100 dB

THD (Total Harmonic Distortion)

- 0.004 %

Signal to Noise Ratio

- 103 dB

Rated RCA Output Level and Impedance

- 2.0 V (rms) / 540 Ω

Audio Output (Digital/Optical)

- -22.5 dBm

Audio Output/Impedance (Digital/Coaxial)

- 0.5 V p-p / 75 Ω

Operation Condition Temperature/Humidity

- 5 ° C–35 ° C / 5 %–85 %

Power Supply

- North American: AC 120 V, 60 Hz
- Japan : AC 100 V, 50/60 Hz
- Other : AC 220–240 V, 50/60 Hz

Power Consumption

- North American: 12W
- Japan : 10W
- Other : 12W

Stand-by Power Consumption

- 0.2 W

Dimensions(W × H × D)

- 435 × 100 × 305 mm (17 1/8 × 4 × 12 3/64 inches)

Weight

- 5.3 kg (11.7 lbs)

Disc Compatibility

- Audio CD, CD-R*, CD-RW*, MP3(CD-R*, CD-RW*)

*Discs that have not been properly finalized may only be partially playable or not playable at all.

Audio Outputs

- Digital Outputs : 2 (OPTICAL ×1, COAXIAL ×1)
- Analog Outputs : 1

Specifications and features are subject to change without notice.

