

# SONANCE

## OMNI-6T

### OUTDOOR OMNIDIRECTIONAL 70V/100V 8 OHM LOUDSPEAKER

**The Sonance OMNI-6T omnidirectional outdoor speaker provides true 360-degree audio coverage in the exceptional Sonance performance the industry has come to expect for both commercial and residential outdoor systems.**

With a 6.5" (165mm) woofer and the 60W Sonance Laminated Core 70V/100V Transformer, the Sonance OMNI-6T is a great complement to Sonance Landscape Series speakers and subwoofers or build a system comprised entirely of Sonance OMNI-6T speakers for the ideal solution for spaces requiring omnidirectional coverage like resort gardens, hotel pool areas, theme parks, outdoor shopping malls or open residential backyards.



#### FEATURES AND BENEFITS

- Four x 1.25" (32mm) Wide-Band Drivers: Best-in-class midrange and treble
- 6.5" (165mm) High Excursion Woofer: Exceptional bass response
- Textured brown enclosure: Designed to blend into ground cover, garden beds and foliage
- Sonance Laminated Core Technology transformer (SLCT): Full-fidelity performance in 70V/100V
- Buriable design: Can be buried up to 8" (203mm) deep, leaving only 6" (152mm) visible above-ground
- Weatherproof construction: Design to handle extremes temperature, moisture and salt air

#### APPLICATIONS

- Outdoor Shopping Malls
- Resort Gardens
- Theme Parks
- Hotel Pool Areas
- Outdoor Dining Areas
- Open Residential Backyards
- Sporting Facilities
- Marinas

## TECHNICAL SPECIFICATIONS

Frequency Range (-10dB)	38Hz - 25kHz
Frequency Range (-3dB)	60Hz - 20kHz
Power Capacity	120 Watts Continuous Program Power, 60 Watts Continuous Pink Noise
Nominal Sensitivity	88 dB
Nominal Coverage Angle	360 degrees horizontal, 160 degrees vertical
Directivity Factor (Q)	2.3
Directivity Index (DI)	3.6 dB
Rated Maximum SPL	107dB @ 1 meter (3.3 feet) average, 113dB peak
Rated Impedance	8 ohms nominal, 6 ohms minimum
Transformer Taps	80W, 40W, 20W and (10W @70V)
Crossover Point	500Hz
LF Driver	6.5" (165mm) Polypropylene Cone, Santoprene Rubber Surround
Wide Band Driver	Four 1.25" (32mm) EPDM dome, Ferrofluid cooled
Input Connectors	Flying Leads
Environmental	Conforms to Mil Spec 810 for humidity, IEC 529, IP-66
Included Accessories	Silicone filled wire nuts
Dimension HxDia	14.5"x 12" (368mm x 305mm)



OMNI-6T  
SKU# 40196

## DIMENSIONAL SKETCHES SPECIFICATIONS

### OMNI-6T

Diameter: 12" (305mm)

Height: 14 1/2" (368mm)

