

Specifications

Playable disc types

Audio CD (including CD-R and CD-RW)

Clock sync input

Connector..... BNC
Input sampling frequency 10 MHz
Input impedance..... 50 Ω
Input level..... Rectangle wave: equivalent to TTL levels
Sine wave: 0.5 to 1.0 Vrms

Digital audio outputs

COAXIAL digital..... 1
Output level 0.5 Vpp
Output impedance..... 75 Ω
OPTICAL digital..... 1
TOS (JEITA RC5720C)

External control

Trigger input 1
(3.5mm mono mini jack)
Input level..... 12 V, 1 mA
Trigger output (through)..... 1
(3.5mm mono mini jack)

General

Power supply
Model for Europe..... AC 220–240 V, 50/60 Hz
Model for U.S.A./Canada..... AC 120 V, 60 Hz
Power consumption..... 4 W
Standby power 0.3 W (in standby mode)
External dimensions (W × H × D, including protrusions)
290 × 84.5 × 248.8 mm (11 1/2" × 3 3/8" × 9 7/8")
Weight 4.0 kg (4 7/8 lb)
Operating temperature range +5°C to +35°C
Operating humidity range 5% to 85% (no condensation)
Storage temperature range..... –20°C to +55°C

Included accessories

Power cord × 1

Remote control (RC-1338) × 1

Batteries for remote control (AAA) × 2

Foot pads × 3

Owner's manual (this document, including warranty) × 1

- For information about the warranty, users living in the USA and Canada should see pages 80–81 and the back cover (warranty document). Users living in Europe and other regions should see page 81
- Specifications and appearance are subject to change without notice.
- Weight and dimensions are approximate.
- Illustrations in this manual might differ slightly from production models.