

| TECHNICAL SPECIFICATIONS

MAIN FEATURES

- | Phono Preamplifier with touch display
- | EQ:
3 curves (RIAA, Decca London, American Columbia) with Enhanced option
- | Subsonic filter:
10Hz/36dB octave
- | Frequency response:
20Hz – 20kHz \pm 0.3dB
Enhanced 20Hz – 50kHz \pm 0.3dB
- | THD (Total Harmonic Distortion):
<0.05% @ 1kHz
- | Signal to noise ratio:
89dB
- | Dynamic response:
105dB

ANALOGUE INPUTS

- 1x RCA** stereo MM/MC
- | Input sensitivity:
0.1mV MC up to 10.0mV MM
- | Input impedance:
9 options [10 Ω , 22 Ω , 47 Ω , 100 Ω , 220 Ω , 470 Ω , 1000 Ω , 22k Ω , 47k Ω]
- | Gain:
MM= 40dB
MC= 60dB
with 4 options [0dB, + 3dB, \pm 6dB]
- | MM capacitance:
220pf

AUDIO OUTPUTS

- 1x RCA** unbalanced
- 1x XLR** balanced
- | Output Impedance:
50 Ω

POWER

- | Power supply:
100-120V or 220-240V, 50/60Hz
- | Power consumption:
10W
- | Standby consumption:
< 0,5W
- | Fuse:
2A T

DIMENSIONS AND WEIGHT

- Dimensions:
200W | 80H | 260D mm
290W | 180H | 390D mm - boxed
- Weight:
Kg. 1.2
Kg. 2.2 - boxed