

Specifications/Specifications/Especificaciones

| Specifications/Specifications/ Especificaciones | B600 | T600 |
|--|--|--|
| Frequency Response On Axis @0 +/- 3db On axis @0 +/- 1 1/2db off Axis @ 30 =/- 1 1/2db LF Cutoff | 50-33,000Hz 55-20,000Hz 55-10,000Hz 35Hz | 24-23,000Hz 30-20,000Hz 30-10,000Hz 20Hz |
| Sensitivity Anechoic Listening Room | 86dB 88dB | 89dB 91dB |
| Impedance Nominal Minimal | 6 Ohms 4 Ohms | 4 Ohms 4 Ohms |
| Input Power Recommended Program | 15-150 Watts 150 Watts | 20-300 Watts 300 Watts |
| Acoustic Design Tweeter | 1" (25mm) Titanium Dome with Ferrofluid | 1" (25mm) Titanium Dome with Ferrofluid |
| Midrange | | 5 1/4" (133mm) Cast Basket Carbon Fibre Cone Rubber Surround |
| Woofers | 6 1/2" (165mm) Cast Basket Carbon Fibre Cone Rubber Surround | 3 x 6 1/2" (165mm) Cast Basket Carbon Fibre Cone Rubber Surround |
| Crossover | 2,200Hz, L4 | 450Hz B3, 1800Hz LR4 |
| Design Type | 2-way system Bass Reflex, Rear facing port | Transitional 3-way system Bass Reflex, Triple Rear facing ports 3 Individual Woofer chambers |
| Dimensions Size (WxHxD) | 9 x 15 1/2 x 11 1/2" 228 x 393 x 298mm | 9 x 41 1/4 x 13 1/2" 228 x 1048 x 343mm |
| Net Weight | 23 lbs 10.4 kg | 77 lbs 34.9 kg |
| Finish | Walnut High Gloss Black | Walnut High Gloss Black |
| Features | Dual, 5-way, Gold-plated Binding Posts, Bi-wireable/Bi-ampable, Magnetic Grille isoAcoustic isolation Feet Rear Facing Port | Triple, 5-way Gold-plated Binding Posts Tri-wireable/Tri-ampable, Magnetic Grille Outrigger stabilizers with isoAcoustic GAIA II feet Port Plug (x2) Subdivided discrete chambers 3 Individual Woofer Chambers Triple Rear Facing Ports |