





Specifications



	Q 3010i	Q 3020i	Q 3050i Floorstanding	Q 3090Ci	Q 3060S
Loudspeaker					
Enclosure Type	2-way reflex	2-way reflex	2-way reflex	2-way reflex	infinite baffle
Bass Unit	100 mm (4in)	125 mm (5in)	2 x 165 mm (6.5in)	2 x 100 mm (4in)	200 mm (8in)
Treble Unit	22 mm (0.9in)	22 mm (0.9in)	22 mm (0.9in)	22 mm (0.9in)	-
Frequency Response (+3 dB, -6 dB)	65 Hz – 30 kHz	64 Hz – 30 kHz	44 Hz – 30 kHz	75 Hz – 30 kHz	35 – 250 Hz
Average Impedance	6 Ω	6 Ω	6 Ω	6 Ω	-
Minimum Impedance	4 Ω	4 Ω	4 Ω	4 Ω	-
Sensitivity (2.83 Vrms@1 m)	86 dB	88 dB	91 dB	89 dB	-
Stereo Amplifier Power	15 – 75 W	25 – 75 W	25 – 180 W	25 – 100 W	-
AV Receiver (2 ch. driven)	50 - 125 W	50 - 125 W	50 - 165 W	50-165 W	-
Internal Amplifier Power	-	-	-	-	150 W Class D
Cross-over Frequency	2.6 kHz	2.4 kHz	2.5 kHz	2.7 kHz	35 – 250 Hz (var)
Effective Volume	4.0 L (244 cu in)	6.1 L (372 cu in)	32.4 L (1977 cu in)	6.6 L (403 cu in)	10.6 L (647 cu in)
Enclosure Dimensions (WxHxD) (inc. grille terminals and feet)	150 x 253 x 252 mm (5.9 x 10.0 x 10in)	170 x 278 x 282 mm (6.7 x 11.0 x 11.1in)	310 x 1020 x 310 mm (12.2 x 40.1 x 12.2in)	430 x 152 x 216 mm (16.9 x 6.0 x 8.5in)	480 x 300 x 150 mm (18.9 x 11.8 x 5.9 in)
Weight (per speaker)	4.1 kg (9.0 lbs)	5.5 kg (12.1 lbs)	17.8 kg (39.2 lbs)	6 kg (13.2 lbs)	8.5 kg (18.7 lbs)
Stock codes	QA3510 Grey QA3512 Walnut QA3516 Black QA3518 White	QA3520 Grey QA3522 Walnut QA3526 Black QA3528 White	QA3550 Grey QA3552 Walnut QA3556 Black QA3558 White	QA3560 Grey QA3562 Walnut QA3566 Black QA3568 White	QA3590 Grey QA3592 Walnut QA3596 Black QA3598 White