

Specification

Specification

Audio performance

Power output:	100W (2 x 25W + 50W) total amplification
THD (at rated power):	<1.00%
Frequency response:	±0.5dB 20Hz to 20kHz
S/N ratio (A-Wtd):	-85dB
Line in 1 (RCA phono) input sensitivity:	2.0Vrms
Line in 1 (RCA phono) input overload:	2.2Vrms
Line in 2 (3.5mm jack) input sensitivity:	1.0Vrms
Line in 2 (3.5mm jack) input overload:	1.2Vrms

Speakers

LR drivers:	BMR 65mm x 65mm
Subwoofer:	Twin coil 100mm x 150mm

Power consumption

Standby:	<0.5 Watts
No signal (idle):	14 Watts
Rear panel marked line ratings:	100~240V - 50~60Hz 100W

Bluetooth®

Bluetooth specification:	V4.0 class 2 device
Latency:	6ms
Internal stereo CODEC:	16-bit
Stereo audio sample rate:	up to 48kHz
Music enhancements:	aptX®, SBC, MP3
Support for:	A2DP, 802.11 co-existence

Dimensions

(W x H x D):	1000mm x 90mm x 142mm
Height including feet:	105mm

Weight

Total weight:	4.9 kg
---------------	--------