

## 212 Black Label Specifications

**Type:** (2)Front-firing active driver, (1) rear passive, (1)down-firing passive radiator

**Active Drive Unit:** (2)12 in. (305mm) long-throw, CarbonAlloy™ cone structure, die cast alloy chassis

**Passive Radiator:** Rear: 12 in., (305mm), CarbonAlloy™ cone structure, die cast alloy chassis;  
Down: 12 in., (305mm)CarbonAlloy™ cone structure, die cast alloy chassis

**Lower Frequency Response in Room:** -6 dB at 18Hz

**Input Connectors:** High Level Neutrik Speakon, Left and Right Low Level phono, LFE phono, LFE XLR

**Output Connectors:** High Level Neutrik Speakon, , Low Level RCA, LFE XLR

**Gain Control Range:** 80 dB

**Power Output:** 1000 watts (RMS)

**Phase Switch:** Yes, 0 or 180 degrees

**Amplifier Type:** Linear Class D

**Wireless capability:** Yes- REL AirShip [required]. Sold separately.

### Protection System

**Fully Electronic with SET-SAFE:** Yes

**D.C. Fault:** Yes

**Output Short:** Yes

**Mains Input Voltage:** 220-240 volts, 110-120 volts for certain markets

**Fuses:** 8 Amp semi delay 220 volts operation, 15 Amp semi delay 120 volts operation

### Dimensions

**W x H x D, Including Feet and Rear Panel Controls:** 14.25 x 33 x 20.5 in., (362 x 840 x 523.3 mm)

Add 1.75in (44.5mm) in depth when using Hi Level connector

**Net Weight:** 134 lbs. (60.8 kg)

**Finish:** Piano Black Lacquer 8 coats

### Supplied Accessories

**Mains Lead:** Yes

**Neutrik Speakon Interconnect 10 Metres Nominal:** Yes

**Users Manual:** Yes