

Carbon Special Black Label Specifications

Type: Front-firing active driver, down-firing passive radiator

Active Drive Unit: 12 in. (305mm) long-throw, carbon fibre cone with inverted carbon fibre centre cap, die cast alloy chassis

Passive Radiator: 12 in., (305mm), Carbon/Carbon flat cone structure, steel chassis

Lower Frequency Response in Room: -6 dB at 19Hz

Input Connectors: High Level Neutrik Speakon, Left and Right Low Level phono, LFE phono, LFE XLR

Output Connectors: High Level Neutrik Speakon, , Low Level RCA, LFE XLR

Gain Control Range: 80 dB

Power Output: 900 watts (RMS)

Phase Switch: Yes, 0 or 180 degrees

Amplifier Type: Linear Class D

Wireless capability: Yes- REL AirShip [required]. Sold separately.

Protection System

Fully Electronic with SET-SAFE: Yes

D.C. Fault: Yes

Output Short: Yes

Mains Input Voltage: 220-240 volts, 110-120 volts for certain markets

Fuses: 8 Amp semi delay 220 volts operation, 15 Amp semi delay 120 volts operation

Dimensions

W x H x D, Including Feet and Rear Panel Controls: 19.25 x 16.125 x 21.25 in., (488 x 410 x 540 mm)

Add 1.75in (44.5mm) in depth when using Hi Level connector

Net Weight: 98 lbs. (44.5 kg)

Finish: Piano Black Lacquer 8 coats

Supplied Accessories

Mains Lead: Yes

Neutrik Speakon Interconnect 10 Metres Nominal: Yes

Users Manual: Yes