G2

Visually stunning, leveraging the design aesthetic of its larger sibling, G-2 provides the power and agility Gibraltar has come to be known for, at a more modest scale than our other reference subwoofers.

Specifications

TYPE	Closed box, front firing driver
ACTIVE DRIVER SIZE & MATERIAL	10 in., 250mm long throw, carbon fibre cone
PASSIVE RADIATOR SIZE & MATERIAL	N/A
LOW FREQUENCY EXTENTION	-6dB at 19 Hz
INPUT CONNECTORS	High-Level Neutrik Speakon, Low Level stereo phono, LFE phono, LFE XLR
OUTPUT CONNECTORS	High Level Low Level RCA Balanced XLR Daisy Chain Outputs
POWER OUTPUT	600 watts (RMS) Ultra High-Current Power Supply
AMPLIFIER TYPE	Class AB
WIRELESS CAPABILITY	N/A

Protection System

FULLY ELECTRONIC SET SAFE	Yes
D.C. FAULT	Yes
OUTPUT SHORT	Yes
MAINS INPUT VOLTAGE	220-240 volts, 110-120 volts for certain markets
FUSES	5 Amp semi delay 230 volts operation, 10 Amp semi delay 115 volts operation

Dimensions

W X H X D	20 x 16.4 x 24 in. (508.8 x 417.3 x 610.4 mm)
NET WEIGHT	84 lbs. (38.1kg)
FINISH	Piano Black Lacquer, 12 coats

Supplied Accessories

MAINS LEAD	Yes
NEUTRIK SPEAKON	Yes
INTERCONNECT	Neutrik Speakon Interconnect (10 Meters Nominal)
USERS MANUAL	Yes

In the interest of product development, REL Acoustics Limited reserve the right to vary these specifications without notice.