

Specifications

Type:	S/5 Front-firing active woofer, down-firing passive radiator
Active Drive Unit:	12 in., 300mm long-throw, pressed Aluminium chassis
Passive Radiator:	12 in., 300mm
Lower Frequency Response in Room:	20Hz at -6 dB
Input Connectors:	Hi Level Neutrik Speakon, Left and Right Lo Level phono, LFE phono, SMA for wireless antenna
Gain Control Range:	80 dB
Power Output:	550 watts (RMS)
Phase Switch:	Yes, 0 or 180 degrees
Amplifier Type:	Next Gen II Class D
REL Longbow Wireless capability:	Yes – REL Longbow™ transmitter [required], Sold separately

Protection System

Fully Electronic with SET-SAFE:	Yes
D.C. Fault:	Yes
Output Short:	Yes
Mains Input Voltage:	220-240 volts, 110-120 volts for certain markets
Fuses (semi delay):	5 Amp 220 volts operation 9 Amp 120 volts operation
Dimensions (W x H x D)*:	17.5 x 18 x 20 in., (444.5 x 455.5 x 507 mm)
Net Weight:	69.7 lbs. (31.6 kg)
Shipping Weight:	79.5 lbs. (36 kg)
Finish (Gloss):	Piano Black White Lacquer

Supplied Accessories

Mains Lead:	Yes
Neutrik Speakon	
Interconnect 10 Metres Nominal:	Yes

* Including Feet and Rear Panel Controls, Add 1.75in (44.5mm) in depth when using Hi Level connector

In the interest of product development, REL Acoustics Limited reserve the right to vary these specifications without notice.