

REL

ACOUSTICS
• LTD •

T/5i Specifications

Type:	Closed Box, down-firing active woofer
Active Drive Unit:	8in., 200 mm long-throw, inverted dust cap, steel chassis
Lower Frequency Response:	32 Hz at -6 dB in room
Input Connectors:	Hi Level Neutrik Speakon, Lo Level single phono, LFE phono
Input Impedance:	High Level: 150k, Low Level: 10k, .1/LFE: 10k ohms
Gain Control Range:	80 dB
Power Output:	125 Watts (RMS)
Phase Switch:	Yes, 0 or 180 degrees
Amplifier Type:	Class AB

Protection System

Fully Electronic SET-SAFE:	Yes
D.C. Fault:	Yes
Output Short:	Yes
Mains Input Voltage:	220-240 volts, 110-120 volts for certain markets
Fuses:	1.6 Amp semi delay 230 volts operation, 3.15 Amp semi delay 115 volts operation
Dimensions (WHD):	10.5 x 12.5 x 12.7 in., (267 x 317 x 322 mm) Including Feet and Rear Panel Controls Add 1.75 in (44.5 mm) in depth when using Hi Level connector
Net Weight:	26.5 lbs. (12 kg)
Finish:	Gloss Piano Black or White Lacquer

Supplied Accessories

Mains Lead:	Yes
Neutrik Speakon Interconnect:	Yes (10 Meters Nominal)
Users Manual:	Yes

In the interest of product development, REL Acoustics Limited reserves the right to vary these specifications without notice.