



Otseajamiga plaadimängijasüsteem SL-1200GR2

Turntable Section

Drive Method	Direct Drive
Motor	Brushless DC motor
Turntable Speeds	33-1/3, 45 and 78 rpm
Pitch Adjustment Range	±8% and ±16%
Starting Torque	2.2 kg·cm
Build-up Characteristics	0.7 s. from standstill to 33- 1/3 rpm
Braking system	Electronic brake
Wow and Flutter	0.025% W.R.M.S.
Turntable Platter	Aluminum diecast Diameter: 332mm Weight: Approx. 2.5kg (Including a rubber sheet)

Tonearm Section

Type	Static Balance
Effective Length	230mm
Overhang	15mm
Tracking Error Angle	Within 2° 32' (at the outer groove of 30cm(12") record) Within 0° 32' (at the inner groove of 30cm(12") record)
Offset Angle	22°
Arm Height Adjustment Range	0 - 6mm
Stylus Pressure Adjustment Range	0 - 4g (Direct Reading)
Headshell weight	Approx. 7.6g

Applicable Cartridge Weight Range	(without auxiliary weight) 5.6 - 12.0g 3.1 - 9.5g (using cartridge spacer) 14.3 - 20.7g (including head shell) (with auxiliary weight) 10.0 - 16.4g 7.5 - 13.9g (using cartridge spacer) 18.7 - 25.1g (including head shell)
--	---

Cartridge Mounting Dimension	12.7 mm (1/2") interval
-------------------------------------	-------------------------

Head Shell Terminal Lug	1.2mmφ 4-pin terminal lug
--------------------------------	---------------------------

Terminals

Audio Output	PHONO (Pin Jack) x 1 EARTH TERMINAL x 1
---------------------	--

General

Power Supply	AC220-240 V, 50/60 Hz
---------------------	-----------------------

Power Consumption	11 W (Power ON) 0.3 W (Power OFF)
--------------------------	--------------------------------------

Dimensions (W x H x D)	453 x 173 x 372 mm
-------------------------------	--------------------

Weight	Approx. 11.5kg
---------------	----------------

Operating temperature range	0°C to +40°C
------------------------------------	--------------

Operating humidity range	35% to 80% RH (no condensation)
---------------------------------	---------------------------------

Accessories	Turntable, Turntable sheet, Dust cover, EP record adaptor, Balance weight, Auxiliary weight, Cartridge spacer Head shell, Overhang gauge, Screw set for cartridge, PHONO cable, PHONO earth lead, AC power supply cord, Owner's Manual
--------------------	--