



Direct Drive Turntable System SL-1210GEG-K

Turntable section

Type	Direct Drive Manual Turntable
Turntable Speeds	33-1/3, 45 and 78 rpm
Adjust Range	±8 %, ±16 %
Starting Torque	3.3 kg-cm
Build-up Characteristics	0.7 s. from Standstill to 33-1/3 rpm
Wow And Flutter	0.025 % W.R.M.S. (JIS C5521)
Rumble	78 dB (IEC 98A weighted)
Turntable Platter	Brass and aluminium die-cast combined Diameter: 332mm Weight: Approx. 3.6 kg (including a rubber mat)

Tonearm Section

Type	Universal Static Balance
Effective Length	230 mm
Overhang	15 mm
Tracking Error Angle	Within 2° 32'(at the outer groove of 30 cm (12") record) Within 0° 32'(at the inner groove of 30 cm (12") record)
Offset Angle	22°
Arm-height Adjustment Range	0 - 6 mm
Stylus Pressure Adjustment Range	0 - 4 g (direct reading)
Head Shell Weight	Approx. 7.6 g
Applicable Cartridge Weight Range	(Without the auxiliary weight) 5.6 to 12.0 g 14.3 to 20.7 g (including the head shell)

(With small auxiliary weight)
10.0 to 16.4 g
18.7 to 25.1 g (including the head shell)
(With large auxiliary weight)
14.3 to 19.8 g
23.0 to 28.5 g (including headshell)

Cartridge Mounting Dimension JIS 12.7 mm Interval

Head Shell Terminal Lug 1.2 mm ϕ 4-pin Terminal Lug

Terminals

Audio Output PHONO (Pin Jack), EARTH TERMINAL

General

Power Supply AC 110 - 240 V, 50 / 60 Hz

Power Consumption 14 W Approx. 0.2 W (standby)

Dimensions (W x H x D) 453 x 173 x 372 mm

Weight Approx. 18 kg

Accessories Turntable, Turntable Mat, Dust Cover, EP Record Adaptor, Balance Weight, Auxiliary Weight Small, Auxiliary Weight Big, Head Shell, Overhang Gauge, Screw Set for Cartridge, PHONO Cable, PHONO Earth Lead, AC Mains Lead, Screw Set for Turntable, Owner's Manual

[Products](#) [Grand Class](#) [Grand class Turntables](#) [SL-1210GEG-K](#)

[Facebook](#) [YouTube](#) [Instagram](#)

[Terms of Use](#) [Privacy Policy](#) [Contact Us](#) [Cookies Policy](#)

[🌐 Area / Country](#)

Copyright © 2024 Panasonic New Zealand