



## Otseajamiga plaadimängijasüsteem SL-1210GR2

### Turntable Section

<b>Drive Method</b>	Direct Drive
<b>Motor</b>	Brushless DC motor
<b>Turntable Speeds</b>	33-1/3, 45 and 78 rpm
<b>Pitch Adjustment Range</b>	±8% and ±16%
<b>Starting Torque</b>	2.2 kg·cm
<b>Build-up Characteristics</b>	0.7 s. from standstill to 33- 1/3 rpm
<b>Braking system</b>	Electronic brake
<b>Wow and Flutter</b>	0.025% W.R.M.S.
<b>Turntable Platter</b>	Aluminum diecast Diameter: 332mm Weight: Approx. 2.5kg (Including a rubber sheet)

### Tonearm Section

<b>Type</b>	Static Balance
<b>Effective Length</b>	230mm
<b>Overhang</b>	15mm
<b>Tracking Error Angle</b>	Within 2° 32' (at the outer groove of 30cm(12") record) Within 0° 32' (at the inner groove of 30cm(12") record)
<b>Offset Angle</b>	22°
<b>Arm Height Adjustment Range</b>	0 - 6mm
<b>Stylus Pressure Adjustment Range</b>	0 - 4g (Direct Reading)
<b>Headshell weight</b>	Approx. 7.6g

<b>Applicable Cartridge Weight Range</b>	(without auxiliary weight) 5.6 - 12.0g 3.1 - 9.5g (using cartridge spacer) 14.3 - 20.7g (including head shell) (with auxiliary weight) 10.0 - 16.4g 7.5 - 13.9g (using cartridge spacer) 18.7 - 25.1g (including head shell)
--	---

<b>Cartridge Mounting Dimension</b>	12.7 mm (1/2") interval
-------------------------------------	-------------------------

<b>Head Shell Terminal Lug</b>	1.2mmφ 4-pin terminal lug
--------------------------------	---------------------------

## Terminals

<b>Audio Output</b>	PHONO (Pin Jack) x 1 EARTH TERMINAL x 1
---------------------	--

## General

<b>Power Supply</b>	AC220-240 V, 50/60 Hz
---------------------	-----------------------

<b>Power Consumption</b>	11 W (Power ON) 0.3 W (Power OFF)
--------------------------	--------------------------------------

<b>Dimensions (W x H x D)</b>	453 x 173 x 372 mm
-------------------------------	--------------------

<b>Weight</b>	Approx. 11.5kg
---------------	----------------

<b>Operating temperature range</b>	0°C to +40°C
------------------------------------	--------------

<b>Operating humidity range</b>	35% to 80% RH (no condensation)
---------------------------------	---------------------------------

<b>Accessories</b>	Turntable, Turntable sheet, Dust cover, EP record adaptor, Balance weight, Auxiliary weight, Cartridge spacer Head shell, Overhang gauge, Screw set for cartridge, PHONO cable, PHONO earth lead, AC power supply cord, Owner's Manual
--------------------	--