



Direct Drive Turntable System SL-1210MK7

Turntable section

Type	Direct Drive Manual Turntable
Turntable Speeds	33-1/3, 45 rpm (with switch 78 rpm)
Starting Torque	0.18 N · m / 1.8 kg · cm
Build-up Characteristics	0.7 s. from standstill to 33 1/3 rpm
Wow And Flutter	0.025 % W.R.M.S.
Turntable Platter	Aluminium diecast Diameter : 332 mm Weight : Approx. 1.8 kg (Including slipmat and slipsheet)

Tonearm Section

Type	Universal Static Balance
Effective Length	230 mm
Overhang	15 mm
Tracking Error Angle	Within 2° 32' (at the outer groove of 30 cm record) Within 0° 32' (at the inner groove of 30 cm record)
Offset Angle	22°
Arm-height Adjustment Range	0 - 6 mm
Stylus Pressure Adjustment Range	0 - 4 g (Direct Reading)
Head Shell Weight	Approx. 7.6 g
Applicable Cartridge Weight Range	(without auxiliary weight) 5.6 - 12.0 g 14.3 - 20.7 g (including head shell)
Head Shell Terminal Lug	1.2 mmφ 4-pin terminal lug

Terminals

Audio Output	PHONO (Pin Jack) x 1, EARTH TERMINAL x 1
---------------------	--

General

Power Supply	AC 110 - 240 V, 50 / 60 Hz
---------------------	----------------------------

Power Consumption	8 W Approx. 0.2 W (Standby)
--------------------------	--------------------------------

Dimensions (W x H x D)	453 x 169 x 353 mm
-------------------------------	--------------------

Weight	Approx. 9.6 kg
---------------	----------------

Accessories	Turntable, Slipmat, Slipsheet, Dust cover, EP record adaptor, Balance weight, Head shell, Screw set for cartridge, PHONO cable, PHONO earth lead, AC power supply cord, Owner's Manual
--------------------	--

[Products](#) [DJ Equipment](#) [SL-1210MK7](#)

[Facebook](#) [X](#) [YouTube](#) [Instagram](#)

[About Us](#) [Terms of Use](#) [Privacy Policy](#) [Cookie Policy](#) [Contact Us](#) [Where to Buy](#)

[🌐 Area / Country](#)

Copyright © 2023 Panasonic UK & Ireland

