



Otseajamiga vinüüplaadimängija SL-1500C

Turntable section

Type	Direct Drive Manual Turntable
Turntable Speeds	33-1/3, 45 and 78 r/min
Starting Torque	0.18 N · m / 1.8 kg · cm
Build-up Characteristics	0.7 s. from standstill to 33 1/3 rpm
Wow And Flutter	0.025 % W.R.M.S.
Turntable Platter	Aluminium diecast Diameter : 332 mm Weight : Approx. 2.0 kg (Including rubber sheet)

Tonearm Section

Type	Universal Static Balance
Effective Length	230 mm
Overhang	15 mm
Tracking Error Angle	Within 2° 32' (at the outer groove of 30 cm (12") record) Within 0° 32' (at the inner groove of 30 cm (12") record)
Applicable Cartridge Weight Range	(without auxiliary weight) 5.6 - 12.0 g 14.3 - 20.7 g (including head shell) (with auxiliary weight) 10.0 - 16.4 g 18.7 - 25.1 g (including head shell)
Head Shell Terminal Lug	1.2 mmφ 4-pin terminal lug

Terminals

Audio Output	PHONO (Pin Jack) x 1 EARTH TERMINAL x 1 LINE (Pin Jack) x 1
---------------------	---

General

Power Supply AC 110 - 240 V, 50 / 60 Hz

Power Consumption 8 W
Approx. 0.2W (Standby)

Dimensions (W x H x D) 453 x 169 x 372 mm

Weight Approx. 9.9 kg

Accessories Turntable, Turntable sheet, Dust cover, EP record adaptor, Balance weight, Auxiliary weight, Head shell, Cartridge(ortofon 2M Red), PHONO cable, PHONO earth lead, AC power supply cord, Owner's Manual

Tooted Premium Class SL-1500C

[Facebook](#) [X](#) [YouTube](#) [Instagram](#)

[Tingimused](#) [Privaatsustingimused](#) [Küpsiste kasutamise poliitika](#)

[🌐 Piirkond / Riik](#)

Copyright © 2023 Panasonic Marketing Europe GmbH

