

# NEWSLETTER

## SV-237MK

### CHANGED..

Our most successful model provides new connection terminals. Technical development is increasing fast nowadays. For this reason, many customers changing also their requests to their amplifier.

That is why the SV-237 has evolved into the SV-237MK. The newest edition of our most successful model has now an optical and a coax digital input instead of a USB port. The converter module works with a bit rate of 24bit/192 kHz for processing high-definition musical files. We have also added an earphone jack to the amplifier.



**SV-237MK**  
integrated Amplifier



# NEWSLETTER

## SV-237MK

The basic design of the SV-237MK is unchanged to its predecessor. Why tinkering around when it is already perfect in that price category?

In the preamp section two Russian 6N61 tubes do their work, adding warmth and authenticity to the sound. The same switches from the predecessor provide an excellent signal-to-noise value. High-end speakers provide a superb playback quality - without any signal noises.



Connections



SV-237MK

## SPECIFICATIONS:

Frequency Response:	20Hz – 20kHz +/-0.5dB; 20Hz – 50kHz +/-2dB
Rated power output to 4 Ohm:	2 x 250 Watt (RMS)
Rated power output to 8 Ohm:	2 x 150 Watt (RMS)
Rated power output Class A to 8 Ohm:	2 x 10 Watt (RMS)
Input sensitivity:	300mV
T.H.D.:	<0.1% (1kHz, 1 Watt)
Signal-to-noise Ratio:	>82,8 dB
Input impedance:	47 kOhm
Inputs:	4 x Stereo RCA, 1 x Optisch, 1 x Coax
Outputs:	1 x Stereo RCA Rec Out, 1 x Stereo RCA Pre Out, 2 x 3.5mm Jack socket (Power Control), 4 x 2 Speaker terminals
Dimensions (WxHxD):	430 x 150 x 435 mm
Weight:	20.4 kg
Tubes:	1 x 12AX7; 2 x 6N1P-EV
Color:	black/silver