



Direct Drive Turntable System SL-40CBT

Turntable Section

| | |
|--------------------------|---|
| Drive Method | Direct Drive |
| Motor | Brushless DC motor |
| Turntable Speeds | 33-1/3, 45 |
| Build-up Characteristics | 0.7 s. from standstill to 33- 1/3 rpm |
| Braking system | Electronic brake |
| Wow and Flutter | 0.025% W.R.M.S. |
| Turntable Platter | Aluminium die-cast Diameter: 300mm Weight: Approx. 1.26kg (Including Turntable mat) |

Tonearm Section

| | |
|----------------------|--|
| Type | Static Balance |
| Effective Length | 230mm |
| Overhang | 15mm |
| Tracking Error Angle | Within 2° 32' (at the outer groove of 30cm record) Within 0° 32' (at the inner groove of 30cm record) |
| Offset Angle | 22° |

Phono equalizer section

| | |
|------|--------|
| Gain | 36.5dB |
|------|--------|

Cartridge section

| | |
|------------|-------------------------|
| Model Name | audio-technica AT-VM95C |
|------------|-------------------------|

Bluetooth® section

| | |
|-----------------------------------|---|
| Bluetooth® system specification | Bluetooth® Ver. 5.4 |
| Wireless equipment classification | Class 1 |
| Supported profiles | A2DP |
| Supported codec | Qualcomm® aptX™ Adaptive, SBC |
| Frequency band | 2.4 GHz Band FH-SS |
| Operating distance | Approx. 10 m Line of sight*1 *1 Prospective communication distance. Measurement environment: Temperature 25 °C / Height 1.0 m |

Terminals

| | |
|--------------|--|
| Audio Output | PHONO (Pin Jack) x 1 EARTH TERMINAL x 1 LINE (Pin Jack) x1 |
|--------------|--|

General

| | |
|-----------------------------|---|
| Power Supply | AC 220 - 240 V, 50/60 Hz |
| Power Consumption | 4 W (Power ON) 0.3 W (Power OFF) |
| Dimensions (W x H x D) | 430 x 128 x 353 mm |
| Weight | Approx. 7.1kg |
| Operating temperature range | 0°C to +40°C |
| Operating humidity range | 35% to 80% RH (no condensation) |
| Accessories | Turntable, Turntable mat, Dust cover, EP record adaptor, Balance weight, Head shell with cartridge, PHONO cable, PHONO earth lead, AC power supply cord, Owner's Manual |