

## Specifications

### SuperSat™ 60/60C

<b>Dimensions:</b>	35 <sup>-1/8"</sup> (89.3 cm) H (W) x 4 <sup>-3/4"</sup> (12.1 cm) W (H) x 2 <sup>-13/16"</sup> (7.2 cm) D
<b>Weight:</b>	11 lbs. (5 kg)
<b>Frequency Response:</b>	50 Hz – 35 kHz
<b>Efficiency:</b>	92 dB
<b>Nominal Impedance:</b>	4Ω (Compatible with 8Ω)
<b>Driver Complement:</b>	Two 4" x 7" quadratic planar low frequency radiators Four 4 <sup>-1/2"</sup> high-definition cast-basket MVPP™ mid/bass drivers One HVFR™ High Velocity Folded Ribbon tweeter
<b>Rec. Amplification:</b>	20 – 300 Watt/channel

### SuperSat™ 50/50C

<b>Dimensions:</b>	26 <sup>-3/4"</sup> (68 cm) H (W) x 4 <sup>-3/4"</sup> (12.1 cm) W (H) x 2 <sup>-9/16"</sup> (6.6 cm) D
<b>Weight:</b>	7 lbs. (3.2 kg)
<b>Frequency Response:</b>	60 Hz – 35 kHz
<b>Efficiency:</b>	92 dB
<b>Nominal Impedance:</b>	4Ω (Compatible with 8Ω)
<b>Driver Complement:</b>	Two 4" x 7" quadratic planar low frequency radiators Two 4 <sup>-1/2"</sup> high-definition cast-basket MVPP™ mid/bass drivers One HVFR™ High Velocity Folded Ribbon tweeter
<b>Rec. Amplification:</b>	20 – 200 Watt/channel

### SuperSat™ 3/3C

<b>Dimensions:</b>	12" (30.5 cm) H (W) x 4 <sup>-3/4"</sup> (12.1 cm) W (H) x 2 <sup>-11/16"</sup> (6.9 cm) D
<b>Weight:</b>	6 lbs. (2.8 kg)
<b>Frequency Response:</b>	80 Hz – 35 kHz
<b>Efficiency:</b>	92 dB
<b>Nominal Impedance:</b>	4Ω (Compatible with 8Ω)
<b>Driver Complement:</b>	Two 4 <sup>-1/2"</sup> high-definition cast-basket MVPP™ mid/bass drivers One HVFR™ High Velocity Folded Ribbon tweeter
<b>Rec. Amplification:</b>	20 – 200 Watt/channel

Specifications are subject to change without notice.