



Spectrum II X6

2½ way bass-reflex floorstanding loudspeaker



KEY POINTS

- 2 x 5" cellulose pulp mid-woofer driver
-  Danish design

DESCRIPTION

The perfect, life-size balance.

Combining the acoustic finesse of bookshelf models with the fullness of a real column.

The Spectrum II X6 features 2½ way ZTL technology combining a 1" dome tweeter and two 5" cellulose mid-woofer drivers.

With a sensitivity of 90 dB and a power handling of 100 W RMS (150 W peak), the Spectrum II X6 retains the minimalist spirit of the range with its sleek design..

Its slim format and controlled weight make it an elegant solution for those seeking acoustic presence and aesthetic discretion.





SPECIFICATIONS

- **Type :** Floorstanding loudspeaker
2□ way
Bass-reflex
- **Power :** 100 W RMS / 150 W Peak
- **Power amplifier :** 20 - 150 W
- **Drive-Units :**
 - Tweeter :** 1" Dome
 - Mid-woofer :** 2 x 5" Cellulose pulp
- **Frequency response :** 50 Hz - 20 kHz (±3dB)
- **Sensitivity :** 90 dB / 1W / 1m
- **Crossover :** 1800 & 2900 Hz 12 dB / 12 dB / 12 dB
- **Nominal impedance :** 6 Ω

DIMENSIONS / WEIGHT

- **Dimensions :** W166 x H900 x D268 mm
- **Net weight :** 12 kg

PRODUCT CODES

- **Finish :** Black
SKU : TANSPE2X6BK **EAN :** 5703959232083
- **Finish :** White
SKU : TANSPE2X6WT **EAN :** 5703959232076

ALSO AVAILABLE



Spectrum II X4



Spectrum II X5



Spectrum II XC



Spectrum II XLCR



Spectrum II XATM



Spectrum II XSW8