

SPECIFICATIONS



Full-automatic Analog Turntable

TN-175
SPECIFICATIONS

Spec description

Turntable section	
Drive System	Belt Drive
Motor	DC Motor
Speed	33- $\frac{1}{3}$ rpm, 45 rpm
Wow and Flutter	0.2% or less
Signal-to-Noise Ratio	67dB or higher (A-weighted, 20kHz LPF)
Platter	Molded resin
Diameter of Platter	290mm
Tonearm section	
Type	Static Balance, Straight
Effective Arm Length	207.9mm
Tracking Force	3.5g
Cartridge section	
Type	VM (equivalent to MM)
Output Voltage	3.5mV (1kHz, 5cm/s)
Tracking Force	3.5g \pm 0.5g
Cartridge Weight	5.0g \pm 0.3g
Head-shell Weight	10g (including Screws, Nuts and Wires)
Phono Equalizer Amplifier	



Please choose your language.



International



Analog Output	
Connector	RCA Pin jack (Gold-plated) × 1 pair
Output Voltage	Phono/Line switchable
Phono Output	2.5mV
Line Output	150mV
General	
Power	AC 100-240V, 50/60Hz
Power Consumption	6.0W (less than 0.2W at Standby)
Overall Dimensions (W × H × D)	16.5" × 4.1" × 14.0" 420 × 105 × 355 mm
Weight	Approx. 7- ³ / ₄ lbs. / 3.5 kg
Accessories	Rubber Mat, EP Adapter, VM-type Cartridge (AT3600L, Pre-installed), Platter, Dust Cover, Hinge × 2, RCA Audio Cable, AC Adapter (GPE053A-120050-Z), Owner's Manual (including Warranty Card for US/Canada)

※ RoHS complied.

※ Specification and design subject to change.



Please choose your language.

