

SPECIFICATIONS



Belt-drive turntable

TN-5BB

SPECIFICATIONS

Spec description

Turntable section	
Drive system	Rotation-detection-type high-precision control belt drive
Motor	DC motor
Rotation speed	33-⅓rpm, 45rpm, 78rpm
Wow and flutter	0.1% or less
Platter	Acrylic, 30cm diameter
Tonearm section	
Arm type	Static-balanced S-shaped tone arm
Effective arm length	223mm
Suitable cartridge weight	3.0 to 12.0g (14 to 23 g including head-shell)
Overhang	18mm
Arm height adjustment range	approx. 6mm
Cartridge section	
Type	MM
Output voltage	5.5 mV (1kHz, 5cm/s)
Tracking force	1.8g
Cartridge weight	7.2g
Included head-shell weight:	11g (including screws, nuts and wires)
Replacement record stylus model	Ortofon 2M Red · Stylus lifespan depends on use conditions but is usually about 1000 hours.



Please choose your language.



International



Balanced	
Connector	XLR × 1 pair
Unbalanced	
Connector	RCA × 1 pair
Power	AC 100 to 240V, 50/60Hz (AC Adapter)
Power Consumption	2.0W or less (0.3W at Standby)
Overall Dimensions (W × H × D)	450 × 148 × 351 mm / 17.1" × 5.8" × 13.8" (with dust cover closed) 450 × 420 × 410 mm / 17.1" × 16.5" × 16.1" (with dust cover open) 450 × 135 × 351 mm / 17.1" × 5.3" × 13.8" (with dust cover removed) Including protrusions (when arm holder at the highest position)
Weight	approx. 10.5kg / 23.2 lbs.
Included accessories	45RPM adapter × 1, Counter Weight × 1, Head-shell (Ortofon 2M Red installed) × 1, Platter × 1, Flat Belt × 1, Pulley Cover × 1, Dust Cover × 1, Hinge × 2, Foot height adjustment washers × 4, Arm height adjustment hex wrench × 1, RCA Audio Cable × 1, Ground wire × 1, AC Adapter (GPE018S-120100-Z) × 1, Cartridge Alignment Gauge × 1, User Manual × 1



Please choose your language.

