

General

Power Supply	AC 120 V, 60 Hz
Power Consumption	8 W Approx. 0.2 W (Standby)
Dimensions (W x H x D)	453 x 169 x 353 mm
Weight	Approx. 9.6 kg
Accessories	Turntable, Slipmat, Slipsheet, Dust cover, Technics sticker for limited edition, EP record adaptor, Balance weight, Head shell, Screw set for cartridge, PHONO cable, PHONO earth lead, AC power supply cord, Control vinyl stickers, Owner's Manual

Terminals

Audio Output	PHONO (Pin Jack) x 1, EARTH TERMINAL x 1
--------------	--

Tonearm Section

Type	Universal Static Balance
Effective Length	230 mm
Overhang	15 mm
Tracking Error Angle	Within 2° 32' (at the outer groove of 30cm (12") record), Within 0° 32' (at the inner groove of 30cm (12") record)
Offset Angle	22°
Arm-height Adjustment Range	0 - 6 mm
Stylus Pressure Adjustment Range	0 - 4 g (Direct Reading)
Head Shell Weight	Approx. 7.6 g
Applicable Cartridge Weight Range	5.6 - 12.0 g (without auxiliary weight), 14.3 - 20.7 g (including head shell)

Turntable Section

Type	Direct Drive Manual Turntable
Turntable Speeds	33-1/3, 45 rpm (with switch 78 rpm)
Starting Torque	0.18 N · m / 1.8 kg · cm
Build-up Characteristics	0.7 s. from standstill to 33 1/3 rpm
Wow And Flutter	0.025% W.R.M.S.
Turntable Platter	Aluminum diecast, Diameter : 332 mm, Weight : Approx. 1.8 kg (Including slipmat and slipsheet)