

Specifications

Triton One.R

Speaker Dimensions:	8" (20.3 cm) W x 16 ⁵ / ₈ " (42.3 cm) D x 54" (137.2 cm) H (is with base installed, no spikes)
Base:	12 ³ / ₈ " (31.4 cm) W x 19 ¹ / ₄ " (50.3 cm) D
Weight:	80 lbs (36.3 kg)
Frequency Response:	13 Hz - 35 kHz
Efficiency:	92 dB
Nominal Impedance:	4Ω (Compatible with 8Ω)
Driver Complement:	Three 5" x 9" long-throw subwoofers coupled to Four 7" x 10" quadratic planar infrasonic radiators Two 5 ¹ / ₄ " high-definition cast-basket mid/bass drivers One High-Gauss Neodymium High-Velocity Folded Ribbon (HVFR) Tweeter
Rec. Amplification:	20 - 650 watt/channel
Built-In Subwoofer Power Amplifier:	1600 Watt SuperSub Subwoofer digital/DSP amplifier
Power Requirements/ Consumption:	Low Voltage Version - 120 V at 50 or 60 Hz / 1600 Watts High Voltage Version - 240 V at 50 or 60 Hz / 1600 Watts (Approved for NA (TUV) and the CE market.)

Specifications are subject to change without notice.