

## Triton Reference Specifications

<b>Dimensions</b> (height is with base installed, no spikes)	9-1/4" (23.36 cm) W x 18-3/4" (47.6 cm) D x 58" (147.27 cm) H  Base: 13-5/8" (34.5 cm) W x 22-1/4" (56.4 cm) D
<b>Weight</b>	Product: 108 lbs (49 kg) / Shipping: 150 lbs (68 kg)
<b>Frequency Response</b>	12 Hz - 35 kHz
<b>Efficiency</b>	93.25 dB
<b>Nominal Impedance</b>	Compatible with 8 ohms
<b>Driver Complement</b>	Three - 6" x 10" Long-Throw Quadratic Reference Subwoofers, coupled to:  Four - 9-1/2" x 10-1/2" Quadratic Planar Infrasonic Radiators  Two - 6" High-Definition Cast-Basket Reference Mid/Bass Drivers  One - High Gauss Reference High-Velocity Folded Ribbon (HVFR™) Tweeter
<b>Recommended Amplification</b>	20 - 750 watt/channel
<b>Built-In Subwoofer Power Amplification</b>	1800 watt SuperSub digital/56 bit DSP Subwoofer Amplifier
<b>Power Requirements/Consumption</b>	Low Voltage Version - 120 V at 60Hz / 1800 Watts High Voltage Version - 240 V at 50Hz / 1800 Watts (Approved for NA (TUV) and the CE market.)