

## Triton Five, Triton Seven Specifications

### TRITON FIVE

### TRITON SEVEN

#### Dimensions

(height is with base installed, no spikes)

6-5/8" (16.8 cm) W (front)  
x 8-1/8" (20.5 cm) W (rear)  
x 12-3/8" (31.3 cm) D  
x 44-1/4" (112.4 cm) H

5-3/4" (14.6 cm) W (front)  
x 7-1/4" (18.3 cm) W (rear)  
x 11" (27.9 cm) D  
x 39-3/4" (101 cm) H

Base: 11" (27.9 cm) W  
x 16-1/2" (41.9 cm) D

Base: 10-1/2" (26.5 cm) W  
x 14-1/2" (36.9 cm) D

#### Weight

Product: 40 lbs (18 kg) /  
Shipping: 56 lbs (25.4 kg)

Product: 32 lbs (15 kg) /  
Shipping: 42 lbs (19 kg)

#### Frequency Response

26 Hz - 35 kHz

29 Hz - 35 kHz

#### Efficiency

90 dB

89 dB

#### Nominal Impedance

Compatible with 8 ohms

Compatible with 8 ohms

#### Driver Complement

Two - 6" High-Definition Cast-Basket  
Mid/Bass Drivers, coupled to:

Four - 8" Planar Sub-Bass Radiators

One - HVFR™ High-Velocity Folded Ribbon Tweeter

Two - 5-1/4" High-Definition Cast-Basket  
Mid/Bass Drivers, coupled to:

Two - 8" Planar Sub-Bass Radiators

One - HVFR™ High-Velocity Folded Ribbon Tweeter

#### Recommended Amplification

15 - 400 watt/channel

10 - 300 watt/channel