



Double-face Remote
RC-1333 included

K-05XD Super Audio CD/CD Player



Analog Audio Outputs: ES-Link Analog / XLR x 1 pair
RCA x 1 pair

Digital Audio Outputs: XLR x 1
Coaxial x 1

Digital Audio Inputs: Coaxial x 1
Optical x 1
USB x 1

Clock Input: BNC x 1

Frequency Response: 5Hz to 70kHz (-3dB)*

S/N Ratio: 110dB (IHF-A)*

Total Harmonic Distortion: 0.0007% (1kHz)*

Power: 120V AC 60Hz, 220-240V AC 50Hz

Overall Dimensions (W×H×D): 445 x 161 x 357 mm (include protrusions)

Weight: 20.7 kg

* SACD 0dB, DSDF: F2, XLR out

- This product is available in two different power supply variations as shown in the chart above. Make sure that the voltage shown on the rear panel matches the AC line voltage in your area.
- The shape of the AC inlet and plug of the supplied power cord depends on the voltage rating and destination country.

Please note that not all models are available in every country. Design and specifications subject to change without notice.
©2023 Esoteric Company. All Rights Reserved. All text, images, graphics and other materials on this brochure are subject to the copyright and other intellectual property rights of Esoteric Company. These materials shall not directly or indirectly be published, reproduced, modified or distributed in any medium. Esoteric is a trademark of TEAC Corporation, registered in the U.S. and other countries. Grandioso is a trademark of TEAC Corporation. All other brand or product names are trademarks or registered trademarks of their respective holders.

ESOTERIC COMPANY

1-47, Ochiai, Tama-shi, Tokyo Japan 206-8530
<https://www.esoteric.jp/en>



Key Features

- Newly designed VRDS-ATLAS "ATLAS 05" Super Audio CD Transport mechanism
- "Master Sound Discrete DAC" – In-house developed FPGA, 64bit/512Fs Delta-Sigma modulator
- "Master Sound Discrete Clock for Digital Player" – in-house discrete clock module
- Our proprietary "ES-Link Analog" current signal transmission output
- "Esoteric-HCLD" output buffer amplifier (slew rate: 2,000V/μs)
- 3 power supply transformers (two toroids for analog, digital and one EI for control)
- Low-feedback DC regulator
- 10MHz external clock input
- Equipped with MQA decoder
- USB DAC function (DSD 22.5MHz / Asynchronous transmission capability)
- Various in/out terminals;
 - Digital inputs: coaxial, optical (192kHz & DoP)
 - Digital outputs: XLR, coaxial
- Selectable digital filter options for PCM, analog FIR filter on/off function for DSD
- RS-232C port, trigger on/off control
- RC-1333 remote controller that can also control Esoteric amplifiers.

Authorized Dealer