

Analog audio inputs

Connectors	XLR connectors × 2 pairs (L/R)
	RCA connectors × 2 pairs (L/R)
Input impedance	XLR: 40 kΩ
	RCA: 20 kΩ
Maximum input signal voltage	XLR: 6 Vrms
	RCA: 3 Vrms

Analog audio outputs

Connectors	XLR connectors × 1 pair (L/R)
	RCA connectors × 1 pair (L/R)
Output impedance	XLR: 50 Ω
	RCA: 100 Ω
Maximum output voltage	XLR: 7 Vrms
	RCA: 3.5 Vrms
Frequency response*	10 Hz to 150 kHz (+1 dB/−4 dB)
S/N ratio*	110 dB (A-Weight, 1 kHz)
THD+N*	0.0006% (1 kHz, LPF: 20 kHz)

*Measurement conditions

Measurement input: RCA, 2 Vrms

Measurement output: RCA, 2 Vrms

Headphone outputs

Connectors	
Standard 6.3mm (1/4") stereo jack	1
3.5 mm (1/8") stereo mini jack	1
4-pin XLR connector	1
4.4mm 5-pole stereo jack	1
Rated output	
Unbalanced (UNBAL)	2.3 W + 2.3 W (into 32 Ω)
	1.2 W + 1.2 W (into 100 Ω)
	0.48 W + 0.48 W (into 300 Ω)
	0.25 W + 0.25 W (into 600 Ω)
Balanced (BAL)	6.7 W + 6.7 W (into 32 Ω)
	4.2 W + 4.2 W (into 100 Ω)
	1.8 W + 1.8 W (into 300 Ω)
	0.95 W + 0.95 W (into 600 Ω)
Applicable load impedance	16 to 600 Ω

External control

Trigger input	1
	(3.5mm mono mini jack)
Input level	12 V, 1 mA
Trigger output	1
	(3.5mm mono mini jack)

General

Power supply	
Model for Europe	AC 220–230 V, 50/60 Hz
Model for USA/Canada	AC 120 V, 60 Hz
Power consumption	30 W
Standby power	0.3 W
External dimensions (W × H × D, including protrusions)	290 × 84.5 × 243.9 mm (11 1/2" × 3 3/8" × 9 5/8")
Weight	4.6 kg (10 1/4 lb)
Operating temperature range	+5°C to +35°C
Operating humidity range	5% to 85% (no condensation)
Storage temperature range	−20°C to +55°C

Included accessories

Power cord	× 1
Remote control (RC-1340)	× 1
Batteries for remote control (AAA)	× 2
Foot pads	× 3
Owner's manual (this document, including warranty)	× 1
- For information about the warranty, users living in the USA and Canada should see pages 44–45 and the back cover (warranty document). Users living in Europe and other regions should see page 45. - Specifications and appearance are subject to change without notice. - Weight and dimensions are approximate. - Illustrations in this owner's manual might differ slightly from production models.	