

Audio performance

Rated output	30 W + 30 W (8 Ω) 60 W + 60 W (4 Ω)
Frequency response	5 Hz – 100 kHz (+0 dB, –3 dB, 8 Ω)
S/N ratio	102 dB (IHF-A, XLR)
Total harmonic distortion	0.007% (1 kHz, 8 Ω, 30 W)
Compatible impedance	4 Ω – 16 Ω In BTL mode. 8 Ω – 16 Ω
Gain	28.5 dB
Damping factor	500
Input connectors	
ESL-A	1 pair
RCA	1 pair
XLR	1 pair
Input impedance	
RCA	47 kΩ
XLR	100 kΩ
Trigger connectors	
IN	1
THROUGH	1

General

Power supply	
Model for Europe	AC 230 V, 50 Hz
Model for USA/Canada	AC 120 V, 60 Hz
Power consumption	250 W (240 W when no signal)
External dimensions (W × H × D, including protrusions)	445 × 191 × 444 mm (17 5/8" × 7 5/8" × 17 1/2")
Weight	30.7 kg (67 3/4 lb)
Operating temperature range	+5°C to +35°C
Operating humidity range	5% to 85% (no condensation)
Storage temperature range	–20°C to +55°C

Included accessories

Power cord	× 1
Felt pads	× 4
Owner's manual (this document)	× 1
Warranty card	× 1

- Specifications and appearance are subject to change without notice.
- Weight and dimensions are approximate.
- Illustrations in this manual might differ slightly from production models.