

System	
Frequency response <sup>1</sup>	34 Hz - 44 kHz (-6 dB)
Recommended amplifier power	20 - 200 W RMS
Power handling (IEC)	100 W continuous, 400 W peak
Nominal dispersion	90 degrees conical
Sensitivity <sup>2</sup>	93 dB (1 W @ 1 m)
Impedance	8 Ω
Maximum SPL <sup>2</sup>	113 dB continuous, 119 dB peak
Components	
Low frequency dual concentric	254 mm (10") with paper pulp cone with twin roll impregnated fabric surround, 52 mm (2") edge wound voice coil
High frequency dual concentric	33 mm (1.3") aluminium/magnesium alloy dome with edge wound voice coil
Crossover	
Frequency	1.3 kHz
Type	Bi-wired, hard-wired passive, low loss 2nd order low pass, 2nd order high pass
Adjustment	±3 dB over 1.3 kHz to 44 kHz shelving
Enclosure	
Type	Dual distributed port
Connectors	5 x 4 mm 24 ct Tannoy customized binding posts
Dimensions (HWD)	950 x 456 x 336 mm (37.4 x 18.0 x 13.2")
Net weight	36.5 kg (80.3 lbs)
Construction	19 mm (¾") MDF with plywood internal bracing, heavily damped
Finish	Walnut veneer and high acoustic transparency nylon grill cover
Accessory pack (included)	
	Bi-wire bridge connectors Prestige wood wax Carpet protectors Adjustable feet Welcome pack documentation

<sup>1</sup> Average over stated bandwidth, measured at 1 metre on axis.

<sup>2</sup> Unweighted pink noise input, measured at 1 metre in half space.