

# Specifications

## Platter

Drive system	Belt drive
Motor	DC motor
Rotation speed	33 1/3 rpm, 45 rpm
Wow and flutter	0.1% or less
SN ratio	67 dB or higher (A-weighted, 20kHz LPF)
Platter	Aluminum die-cast 30cm (12") diameter

## Tonearm

Tonearm type	Static-balanced S-shaped tonearm
Effective tonearm length	223 mm
Tracking force variation range	0–5 g
Acceptable cartridge weight	3.0–12 g 14–23 g (with the included headshell)

## Cartridge

Type	VM (equivalent to MM)
Output voltage	4.0 mV (1 kHz, 5 cm/s)
Tracking force	1.8–2.2 g (2.0 g recommended)
Cartridge weight	6.1 g
Included headshell weight	11 g (including screws, nuts and wires)

- The need for stylus replacement depends on use conditions, but we recommend replacement after about 300 hours of use.
- An Audio-Technica AT-VM95E VM Type cartridge is installed in this unit.  
(The body of the replacement stylus for the installed cartridge is green.)  
Note: VM type cartridges have the same characteristics as MM type cartridges.
- Replacement stylus model: Audio-Technica AT-VMN95E

## Output voltage

PHONO EQ THRU	4.0 mV (1 kHz, 5 cm/s)
PHONO EQ ON	224 mV (–13 dBV)
Output connectors	RCA

## General

AC adapter power	
Input	AC 100 V – AC 240 V, 50/60 Hz
Output	DC 12 V, 500 mA
Power consumption	
Standby	0.5 W or less
On (33, 45)	2.0 W or less
Weight	5.0 kg (11 1/8 lb)
Operating temperature range	5°C to 35°C
Dimensions (W × H × D) (including protrusions)	
When the dust cover is closed	420 × 117 × 356 mm (16 5/8" × 4 5/8" × 14 1/8")
When the dust cover is open	420 × 381 × 402 mm (16 5/8" × 15" × 15 7/8")
When the dust cover is removed	420 × 102 × 356 mm (16 5/8" × 4 1/8" × 14 1/8")

- Performance data is specified at 20°C.

## Included items

Felt mat	× 1
45 RPM adapter	× 1
Counterweight	× 1
Headshell	× 1
Audio-Technica VM type (dual magnet) stereo cartridge (AT-VM95E) preinstalled	

Platter	× 1
Flat belt	× 1
Pulley cover	× 1
RCA audio cable with grounding terminal	× 1
AC adapter (GPE053A-V120050)	× 1
Owner's manual (this document)	× 1

- See the back of this document for warranty information.

- Specifications and appearance are subject to change without notice.
- Weight and dimensions are approximate.
- Illustrations in this owner's manual might differ slightly from production models.